

# Dies for Standard Lugs & Splices (TBM6H – 21940)

CONNECTOR SIZE				BPLT15BSCR / TBM15I****	
CODE COPPER	FLEX/24	AL/CU	COLOR-KEYED DIE COLOR	DIE CAT. NO.	DIE CODE NO.
8 AWG	37/24	10 AWG	RED	15520	21
6 AWG	61/24	8 AWG	BLUE	15522	24
4 AWG	91/24	6 AWG	GRAY	15527-CK	29
2 AWG	125/24		BROWN	15528	33
1 AWG	140/24	4 AWG	GREEN	15513-CK	37
1/0	225/24	2 AWG	PINK	15508	42H
2/0	275/24		BLACK	15526	45
3/0	325/24		ORANGE	15530	50
4/0	450/24		PURPLE	15511	54H
250 kcmil	550/24		YELLOW	15510-CK	62
		1 AWG	GOLD	15526	45
		1/0	TAN	15530	50
		2/0	OLIVE	15511	54H
		3/0	RUBY	15532-CK	60
300 kcmil		4/0	WHITE	15534	66H
350 kcmil	775/24(short)	250 kcmil	RED	15514-CK	71H
400 kcmil	775/24(long)	300 kcmil	BLUE	15512	76H
	925/24*		N/A	15517	80H
			N/A	15606	80
500 kcmil		350 kcmil	BROWN	15506	87H
600 kcmil	1100/24	400 kcmil	GREEN	15611	94H
			GREEN	15536-CK	94H
	1325/24**		PINK		
700 kcmil		500 kcmil	PINK	15505	99H
750 kcmil		650 kcmil	BLACK	15515-CK	106H
800 kcmil			ORANGE	15608	107H
		700 kcmil	PURPLE	15609	112H
900 kcmil	1925/24	750 kcmil	YELLOW	15504	115H
1000 kcmil		800 kcmil		15603	125H
		1000 kcmil		15602	140H
				15601	150H